

GALVANIZED STEEL FLEXIBLE CONDUITS

PRODUCT TYPE

LIQUID-TIGHT TYPE FLEXIBLE STEEL CONDUIT (BLACK-GRAY)

PRODUCT CODE

MLY..

MANUFACTURER

MSM

MATERIAL

GALVANIZED STEEL SHEET

COATING

PVC INSULATION COATED



CERTIFICATES



MSM Code Black	MSM Code Gray	MSM Code Economic	Size	Inside Diameter (mm)	Outside Diameter (mm)	Meters Per Roll (mt)
MLY-10	MLY-10.G	MLY-10.E	1/4"	10	14	30
MLY-13	MLY-13.G	MLY-13.E	3/8"	13	17	30
MLY-16	MLY-16.G	MLY-16.E	1/2"	16	21	30
MLY-21	MLY-21.G	MLY-21.E	3/4"	21	26	30
MLY-26	MLY-26.G	MLY-26.E	1"	26	32	30
MLY-35	MLY-35.G	MLY-35.E	1 1/4"	35	41	15
MLY-40	MLY-40.G	MLY-40.E	1 1/2"	40	47	15
MLY-52	MLY-52.G	MLY-52.E	2"	52	59	15
MLY-63	MLY-63.G	MLY-63.E	2 1/2"	63	72	15
MLY-78	MLY-78.G	MLY-78.E	3"	78	88	7,5
MLY-102	MLY-102.G	MLY-102.E	4"	102	112	7,5

Usage Areas

Due to its acid, oil and water resistance it is especially used in construction of industrial facilities, suitable for outside use. There is a cord inserted in the conduit in order to increase its bending durability.