

RSC TYPE THREADED GALVANIZED STEEL CONDUITS (HEAVY-DUTY TYPE)

PRODUCT TYPE	RSC GALVANIZED STEEL THREADED RIGID CONDUITS
PRODUCT CODE	RSC-301
MANUFACTURER	PRO-STAR
MATERIAL	GALVANIZED STEEL
COATING	HOT-DIP GALVANIZED



GENERAL FEATURES:

- * Certified by UL 6, ANSI C80.1, GOST-R, EAC and CE.
- * Burr-free electrical installation conduits.
- * Produced in the Far East, bendable featured.
- * $\pm 5\%$ tolerance of all below mentioned physical characteristics.
- * Standard product length 3.00 m, has a coupling on one end.

CERTIFICATES



MSM Code	Manufacturer's Code	Thread Size	Nominal Diameter (ID x OD, mm)	Nominal Wall Thickness (mm)	Weight (m/kg)	Quantity per Bundle (pcs)
RSC-301	RGD-050	1/2"	16,02 x 21,30	2,64	1,10	10
RSC-302	RGD-075	3/4"	21,26 x 26,70	2,72	1,40	10
RSC-303	RGD-100	1"	27,00 x 33,40	3,20	2,20	5
RSC-304	RGD-125	1-1/4"	35,44 x 42,20	3,38	3,10	5
RSC-305	RGD-150	1-1/2"	41,28 x 48,30	3,51	3,60	5
RSC-306	RGD-200	2"	52,88 x 60,30	3,71	4,90	3
RSC-307	RGD-250	2-1/2"	63,20 x 73,00	4,90	7,60	3
RSC-308	RGD-300	3"	78,48 x 88,90	5,21	9,80	2
RSC-309	RGD-400	4"	102,86 x 114,30	5,72	14,10	2
RSC-310	RGD-500	5"	128,86 x 141,30	6,22	19,00	1
RSC-311	RGD-600	6"	154,78 x 168,30	6,76	24,90	1

Usage Areas

Especially used in construction of heavy industry facilities (steel and concrete plants), refineries, power plants, facilities with explosion-proof installations. Suitable for underground, outdoor and indoor use.